



Max Floor



Anti-bacteria



Fireproof



Easy Installation



Anti-slip



Easy to Clean



Formaldehyde Free



Sound Insulation



100% Water Proof



Stable to Heat & Sunlight



Perfect for Every Room



Kid and Pet Friendly



Suitable for Underfloor Heating



Max Floor Mountain
180x1200mm



Max Floor Driftwood Grey
180x1200mm




Max Floor Scandinavian Wood
180x1200mm

Size: 180mm x 1220mm x 5.5mm

Wear Layer: 0.5mm



Max Floor Amazon Wood
180x1200mm




Max Floor Ebony Bark
180x1200mm



Max Floor Stonewood Grey
180x1200mm

Max Floor



Product Item	
Material	Premium Stone-Based Flooring (SPC)
Size	180mm x 1220mm x 5.5mm
Thickness	5.5mm
Wear Layer	0.5mm
Underlayment	IXPE

Properties	Standard	Results
Abrasion Group	GB / T 4085-2015	T
Residual Indentation	ISO 24343-1(EN 433)	≤ 0.1mm
Effect Of Simulated Movement from Furniture	EN 424	Pass
Castor Chair Suitability	ISO 4918(EN 425)	Pass
Dimensional Stability and Curling after Exposure to Heat	ISO 23999(EN 434)	≤ 2mm
Dimentional Stability	ISO 23999(EN 434)	≤ 0.25%
Colour Fastness	ISO 105-B02	6
TVCO Regulation After 28 Days	ISO 16000	<100 μg/m ³
Impact Resistance	ASTM F1265 ASTM D3384	Qualified
Slip Resistance	DIN 51130	R10
Fire Resistance	EN ISO11925-2/EN13501-1/EN ISO9239-1	Bfl-S1

Size: 180mm x 1220mm x 5.5mm
Wear Layer: 0.5mm

