

Instructions for Copper and Aluminium MosaicFX Range

Installation Care and Handling :

Handling in transport and installation can always leave minor marks and blemishes on the surface of any metal mosaic. This may be friction and rub mark, subtle grout abrasion, handling impacts. We do not consider these to be faults but rather a natural overall effect. Metal mosaics in Aluminium and Copper will never be perfect. Please select another item if this is your expectation.

MosaicFX Copper Mosaics:

To produce metal copper mosaics, a process of natural oxidation process is used to ensure the natural look of copper. As the metal ages, and according to different conditions, the surface will change over time. This includes natural patina and in more extreme situations, Verdigris will develop. This is a normal aging process in high moisture / oxygen and sulphur conditions. It may be possible to polish back the copper to desired look.

Copper is a soft metal which is not resistant to acid or alkali, these factors will change the colour and appearance of the natural metal.

MosaicFX metal mosaics are not designed for floor use or areas with higher than usual wear.

MosaicFX Aluminium Mosaics:

An aluminium mosaic surface is naturally soft and is NOT abrasion resistant. Must be used on walls only. Any contact with acid or alkali onto the Aluminium mosaic surface should be avoided. In the event that acid or alkali chemicals, cleaner etc do come in contact, immediately wash and rinse with plenty of water, then wipe up clean with a soft, clean cloth.

MosaicFX metal mosaics are not designed for floor use or areas with higher than usual wear.

Daily use and maintenance:

Never use metal mosaics on floors or high wear areas.

Do NOT use abrasive cleaning materials, nor any alkaline or acidic cleaners.

Residual water, if left to evaporate has the potential to watermark. Any cleaner must be PH neutral and applied with soft cleaner cloth / sponge.